

NSWC/WOL TR 77-154

ANALYSIS OF 2,2',4,4',6,6'—
HEXANITROSTILBENE (HNS) BY HIGH
PERFORMANCE LIQUID CHROMATOGRAPHY

DC FILE COPY

BY ELEONORE G. KAYSER

RESEARCH AND TECHNOLOGY DEPARTMENT

14 MARCH 1978

Approved for public release, distribution unlimited.





NAVAL SURFACE WEAPONS CENTER

Dahlgren, Virginia 22448 • Silver Spring, Maryland 20910

78 07 07 102

UNCLASSIFIED SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered) READ INSTRUCTIONS BEFORE COMPLETING FORM REPORT DOCUMENTATION PAGE 2. GOVT ACCESSION NO. 3. RECIPIENT'S CATALOG NUMBER NSWC/WOL/TR-77-154 5 TYPE OF REPORT & PERIOD COVERED TITLE (and Subtitle) ANALYSIS OF 2,2',4,4',6,6'-HEXANITROSTILBENE (HNS) BY HIGH PERFORMANCE LIQUID CHROMATOGRAPHY Final Report. 6. PERFORMING ORG. REPORT NUMBER 8. CONTRACT OR GRANT NUMBER(s) AUTHOR(s) Eleonore G./Kayser 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NASA & NIF; 0; 0; PERFORMING ORGANIZATION NAME AND ADDRESS Naval Surface Weapons Center CR12JC & WR12KA : White Oak, Silver Spring, Maryland 20910 2. REPORT DATE 11. CONTROLLING OFFICE NAME AND ADDRESS 14 March 1978 25 14. MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office) 15. SECURITY CLASS. (of UNCLASSIFIED 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE 16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

HNS

HNS By-product Analysis

Hexanitrostilbene

HPLC Analysis of Explosives

HNS Analysis

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

A high performance liquid chromatographic (HPLC) method for the determination of HNS is described. A reverse-phase micro column was used with a methanol/distilled water mobile phase in a ratio of 2:3 by volume. This method is capable of separating all known by-product impurities resulting from the preparation of HNS by the "Shipp Process". Assays of HNS and 2,2',4,4',6,6'-Hexanitrobibenzyl (HNBiB), the major impurity, can be obtained in less than 40 minutes. Accurate analyses (+ 2%) of HNS and all known by-products can be made in about 90 minutes.

DD 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE S/N 0102-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

391 596

ach

UNCLASSIFIED	
SECURITY CLASSIFICATION OF THIS PAGE(When Date	Entered)

SUMMARY

This report describes an analytical procedure for the assay and analysis of HNS-I and HNS-II using HPLC. Assays of HNS and HNBiB can be obtained in less than 40 minutes. Accurate analyses of HNS and all other known by-products can be made in about 90 minutes. This work was carried out under two tasks, WR12KA, "HNS Explosive Evaluation" for the National Aeronautics and Space Administration, Lyndon B. Johnson Space Center, Houston, and CR12JC, "HNS Explosive Characterization" for the Naval Air Systems Command.

Julius W. Enig JULIUS W. ENIG By direction

DC Buff Section UNANNOUNCED USTIFICATION BY DISTRIBUTION AVAI ARE FIT CO	
USTI KATION	
sy	
0	313

NSWC/WOL TR 77-154

CONTENTS

		Page
ı.	INTRODUCTION	5
II.	EXPERIMENTAL	7
III.	RESULTS AND DISCUSSION	9
IV.	CONCLUSION	10
	TABLES	
Table	<u> </u>	Page
1	Compounds Identified as Products of the TNT-NaClO Reaction	11
2	Average Retention Times and Response Factors for Compounds Isolated from the TNT-NaClO Reaction	13
3	Quantitative HNS Data	14

NSWC/WOL TR 77-154

ILLUSTRATIONS

Figure		Page
1	HPLC Trace of DMSO	15
2	HPLC Trace of a Synthetic Mixture of Potential HNS Impurities	16
3	HPLC Trace of a Synthetic Mixture of Potential HNS Impurities	17
4	HPLC Trace of a Synthetic Mixture of Potential HNS Impurities	18
5	HPLC Trace of a Synthetic Mixture of Potential HNS Impurities	19

I. INTRODUCTION

In recent years, research in polynitroaromatic chemistry at the Naval Surface Weapons Center, White Oak Laboratory, has produced several new high energy compounds that have found numerous applications in military ordnance items and in the National Aeronautics and Space Administration (NASA) space programs including the Space Shuttle. One of these compounds is 2,2',4,4',6,6'-hexanitrostilbene (HNS) which has been shown to be an exceptionally good explosive for high temperature applications in detonation transfer lines and cutting devices using flexible linear shaped charges.

HNS is commercially prepared by reacting 2,4,6-trinitrotoluene (TNT) with a 5 percent aqueous sodium hypochlorite solution (${\rm Clorox}^1$) in the presence of tetrahydrofuran and methanol². The yield of HNS from this reaction is less than 50 percent. The remainder of the TNT is converted to a red-tar fraction of which 80 weight percent has been separated and identified using a combination of thin layer chromatography (TLC) and nuclear magnetic resonance spectroscopy (NMR), Table 1³.

Two types of HNS are used; HNS-I (crude HNS) which is the direct reaction product with minimal purification, and HNS-II (recrystallized HNS). HNS-II has the larger particle size (therefore the smaller surface area) and is required by the Navy Specification WS-5003 to have a bulk density above 0.45 g/cm³,

Commercial household bleach (5.25% sodium hypochlorite) manufactured by the Clorox Company.

²Shipp, K. G., and Kaplan, L. A., "Reaction of α -Substituted Polynitrotoluenes," J. Org. Chem., Vol. 31, 857 (1966).

³Kayser, E. G., this Center, unpublished results.

whereas, HNS-I particles are small (large surface area) and have a bulk density ranging from 0.15 to 0.35 g/cm³ ⁴. Methods for converting HNS-I to HNS-II include (a) extraction with a mixture of acetonitrile and toluene⁵, and (b) recrystallization by a nitric acid process^{6a}, or from fuming nitric acid^{6b}, or dimethylformide⁵.

Although HNS-I is used in a variety of mile ary applications, no general assay method has been available due to (a) the relative insolubility of HNS in most solvents, and (b) the presence within the HNS crystals of trapped by-products from the TNT-NaClO reaction, and interfere with the usual spectrophotometric methods of analysis.

The absorption spectrum of HNS is nonspecific and difficult to distinguish from the absorption contributed by the known redtar components. HNS can be analyzed spectrophotometrically by the ethylene diamine (EDA)/dimethylsulfoxide (DMSO) procedure only after a preliminary purification, for example, by TLC.

At the present time the HNS specification WS-5003 establishes the only requirements for Navy procurement of HNS. The chemical and physical tests include melting point, melting point range, vacuum stability, surface moisture, volatile material, water soluble material, and bulk density. Performance tests include sensitivity and output compared to a "Standard Comparison Sample" (SCS) of either HNS-I or HNS-II. No assay or analysis of material purity is included.

⁴O'Keefe, D. M., "Digestion as a Process Aid for Hexanitrostilbene," Sandia Corporation Report SAND-0330, Feb 1977.

⁵Taylor, F., and Oesterling, R. E., "Heat Resistant Explosives, XX. Production of Grade II HNS," NOLTR 65-142, 26 Aug 1965.

^{6 (}a) Such a process has been used at Teledyne McCormick Selph and at Chemtronics, Incorporated; (b) J. Dacons, unpublished results.

⁷Glover, D., and Kayser, E. G., "Quantitative Spectrophotometric Analysis of Polynitroaromatic Compounds by Reaction with Ethylenediamine," Analytical Chemistry, Vol. 40, 2055 (1968).

An HPLC method 8 for analyzing purified HNS samples and also a semi-quantitative method for analyzing crude samples has been developed using three columns packed with Corasil II 9 and a solvent system consisting of 20% ρ -dioxane/80% n-heptane. This report describes an HPLC method for the quantitative analysis of both HNS-I (crude HNS) and HNS-II (recrystallized HNS) using a reverse-phase micro column. The method does not require gradient elution and can differentiate HNS from any of the other known by-products (Table 1) formed in the "Shipp Process". This method is recommended for inclusion in the Navy HNS specification.

II. EXPERIMENTAL

A. Apparatus

A model ALC 202 Liquid chromatograph equipped with a model 6000 solvent delivery system and a U6K high pressure loop injector (Waters Associates, Milford, Massachusetts) was used for the analyses and the eluent was continuously monitored with a 254 nm UV detector. Qualitative data were obtained on a Waters C-18 reverse-phase Bondapak column (3.2 nm O.D. x 61 cm) with a 37-75 micron particle size. All quantitative data were obtained using a Whatman micro column. A Whatman HPLC guard column containing CO:PELL® ODS pellicular material was used as a precolumn to a Whatman Partisil the bonded reversed-phase column (25 cm x 4.6 nm x 1/4"). The typical efficiency of this analytical micro column is 18,000 plates per meter with octadecyl silane (ODS) functionality. The UV absorption signals were recorded on a Omniscribe strip chart recorder set at 0.5 cm/minute.

Stull, T. W., "Synthesis of High Purity HNS," MHSMP-75-37, Sep 1975.

Waters Associates, Inc., Framingham, Maine.

Registered trademark of Whatman, Inc.

tm trademark of Whatman, Inc.

B. Reagents and Chromatographic Conditions

The mobile phase consisted of methanol (Fisher Scientific, certified A.C.S. grade) and distilled water in a ratio of 2:3 by volume. Pressures at the column head were about 900 psi, 2,000 psi, and 3,000 psi for flow rates of 1 ml, 2 ml, and 3 ml per minute respectively. Column temperature was about 25°C or room temperature. All solvents were filtered twice through a #42 Whatman paper filter prior to use in the HPLC. Samples of 10 to 100 μ l were introduced by syringe injection through the septum.

C. Preparation of Standards and Samples

The compounds (Table 1) isolated from the red-oil produced in the preparation of HNS by the "Shipp Process" were recrystallized and purified by TLC prior to their use as HPLC standards. After drying, approximately 1 mg of each standard was accurately weighed using a Mettler Micro Gram-atic balance and placed in a 10 ml volumetric flask. Each standard and sample was diluted to volume with Fisher A.C.S. grade DMSO, just prior to analysis, to prevent possible solution photolysis. An HPLC trace of DMSO (Figure 1) was run to determine its retention time and the presence of any peaks which could interfere with this method of HNS analysis. p-dioxane was also tried as an HNS solvent but was found unsatisfactory. All sample and standard solutions were prefiltered through a 0.5 μm filter (Waters Clarification Kit) prior to injection in the HPLC.

D. Calculations

The concentration of each material was determined by peak height as well as peak area. As expected, the percentage accuracy for the area method was found to be greater than that of the peak height method. Thus, for quantitative work the area method was used. The response factor for each compound was determined by manually integrating the area of the chromatographic peak of a standard of known concentration. These relative response factors are summarized in Table 2.

III. RESULTS AND DISCUSSION

In preliminary experimental work with a Waters C-18 reverse-phase column, relatively good separations of hexanitrobibenzyl (HNBiB), hexanitrostilbene (HNS), trinitrobenzyl chloride (PiCH2Cl), and trinitrotoluene (TNT) were obtained (Figure 2). However, trinitrobenzene (TNB) was only partially resolved, and trinitrobenzaldehyde (PiCHO) and trinitrobenzyl alcohol (PiCH2OH) remained unresolved.

An improved separation of potential HNS impurities 10 was obtained with a Whatman micro column. As seen in Figures 3 and 4 as well as in Table 2, Picric Acid (PiOH), PiCHO, dinitroanthranil (Anil), TNT, Picryl chloride (PiCl), PiCH₂Cl, HNS, and HNBiB are well separated and the peaks are easily quantified. However, the separation of PiCOOH and TNB was less satisfactory. The PiCOOH eluted just prior to the TNB peak resulting in only a partial resolution of the two components. At a flow rate of 1.0 ml per minute, the average retention time for the last compound, HNBiB, was about 165 minutes.

At a flow rate of 2 ml per minute (Figure 4) separation was still sufficient for quantitation of all compounds except, as expected, PiCOOH and TNB. The average retention time of HNBiB was decreased by about 75 minutes leading to a more rapid method of assay and analysis. When the flow rate was increased to 5 ml per minute, only TNT, PiCH₂Cl, HNS, and HNBiB could be quantitatively determined (Figure 5), but the total sample retention time was decreased to about 40 minutes.

Decreasing or increasing the concentration of methanol in the mobile phase had the same effect on sample separation as a

 $^{^{10}\}mathrm{Synthetic}$ mixture containing all compounds listed in Table 1 except chloropicrin.

flow rate change (i.e., increasing the methanol concentration decreased the average retention time of the sample peaks while a decrease in methanol concentration increased the retention time.) The most complete sample separation in the shortest time resulted with the 40:60 methanol/water eluent at a flow rate of 2 ml per minute. Data obtained from several production grade samples of HNS-I and HNS-II are given in Table 3. The percent composition of each HNS sample was obtained (a) from previously determined response factors, and (b) from the area of the peak alone without the use of comparison standards. For the production grade HNS samples tested, our results show that the area method can be used to determine with sufficient accuracy the percent composition of both HNS-I and HNS-II.

The HNS-I samples were found to contain about 5% HNBiB with minute amounts (<0.1 to 0.2%) of TNB and PiCH₂OH. Since only a partial separation of TNB and PiCOOH was achieved with HPLC, the presence of trace quantities of PiCOOH was determined by TLC; none was found. The HNS-II samples contained between 0 to 3% HNBiB and only possible trace quantities (<0.1%) of the other impurities. Neither TNT nor PiCH₂Cl was found in any of the production grade HNS samples tested.

IV. CONCLUSION

The method detailed in this report permits rapid quantitative determinations of HNS and its primary contaminant HNBiB. Sensitivity is sufficient for reliable determinations in small volumes (50 - 100 μ l) of DMSO solutions. This method can also be used to quantitatively determine all other known by-products resulting from the preparation of HNS by the "Shipp Process".

TABLE I COMPOUNDS IDENTIFIED AS PRODUCTS OF THE TNT-NaCIO REACTION

$$O_{2}N \xrightarrow[]{H} NO_{2}$$

$$O_{3}N \xrightarrow[]{H} NO_{2}$$

$$O_{4}N \xrightarrow[]{H} NO_{2}$$

$$O_{4}N \xrightarrow[]{H} NO_{2}$$

$$O_{5}N \xrightarrow[]{H} NO_{2}$$

TABLE I (CONTINUED)

Pi = 2,4,6 - TRINITROPHENYL

(a) DETERMINED BY GAS CHROMATOGRAPHY (GC), ALL OTHER COMPOUNDS DETERMINED BY NMR.

TABLE 2 **AVERAGE RETENTION TIMES AND RESPONSE FACTORS** FOR COMPOUNDS ISOLATED FROM THE TNT-NaCIO REACTION

	RETEN	RETENTION TIME AT RATE OF		AVERAGE RESPONSE	AVERAGE RESPONSE FACTOR (NORMALIZED	
COMPOUND	1 ML/MINUTE	2 ML/MINUTE	3 ML/MINUTE	FACTOR (a)	TO TNB = 1.0)	
PiOH	2.3	1.1	0.9	(ь)	(ь)	
DMSO (c)	3.5	1.9	1.2	(b)	(b)	
PiCH ₂ OH	9.4	4.8	3.4	764,300	0.82	
PICHO	14.2	7.1	4.9	620,150	0.67	
PiCOOH	16.8	8.3	6.0	(b)	(b)	
TNB	17.4	8.5	6.0	927,100	1.00	
ANIL	23.1	12.1	(b)	(b)	(b)	
PiCI	31.8	15.9	10.9	(b)	(b)	
TNT	33.6	17.3	12.2	808,950	0.87	
PiCH ₂ CI	53.3	26.3	18.0	779,700	0.84	
HNS	98.7	60.0	36.0	875,000	0.94	
HNBiB	162.5	90.0	60.0	886,400	0.95	

CONDITIONS:

PARTISIL-10 ODS-2 (REVERSED PHASE) COLUMN

RANGE 80

5-50µl

SAMPLE VOLUME

SAMPLE

HPLC STANDARDS

SOLVENT

40% METHANOL/60% WATER

COLUMN PRESSURES

1 ML/MINUTE

900-1000 PSI

2 ML/MINUTE

2000 PSI

3 ML/MINUTE

3000 PSI

- (a) RESPONSE FACTOR DETERMINED FROM THE PEAK AREA OF THE STANDARD
- (b) NOT DETERMINED
- (c) HNS SOLVENT

TABLE 3

QUANTITATIVE HNS DATA

% COMPOSITION DETERMINED FROM RESPONSE FACTORS

EXPLOSIVE TYPE	IDENTIFICATION (a)	% HNS	% HNBiB	% TNB (b)	% PiCH ₂ OH
HNS-I	I.D. # 2297 (UTC LOT #3)	95.3	4.6	0.1	(c)
HNS-I	I.D. # 2294 (UTC LOT #1)	94.9	4.9	0.1	0.1
HNS-I	(d)	94.6	5.3	(c)	0.1
HNS-I	(d)	94.9	4.9	0.1	(c)
HNS	I.D. # 2276 (NSWC 96-8433-50 ^(e))	100.0	0.0	0.0	0.0
HNS-II	(d)	98.2	1.8	0.0	(c)
HNS-II	I.D. # 2299 (SILAS MASON HANGER- PANTEX LOT 6348-074-001)	100.0	0.0	(c)	(c)
HNS-I	(BRITISH - PERME 343)	97.3	2.5	0.2	0.1

% COMPOSITION DETERMINED FROM PEAK AREA

EXPLOSIVE TYPE	IDENTIFICATION (a)	% HNS	% HNBiB	% TNB (b)	% PiCH ₂ OH
HNS-I	I.D. # 2297 (UTC LOT #3)	94.4	5.5	(c)	0.1
HNS-I	I.D. # 2294 (UTC LOT #1)	94.6	5.2	0.1	0.1
HNS-I	(d)	94.8	5.1	0.1	0.1
HNS-I	(d)	95.1	4.9	(c)	0.1
HNS	I.D. # 2276 (NSWC 96-8433-50 ^(e))	100.0	0.0	0.0	0.0
HNS-II	(d)	98.3	1.7	(c)	(c)
HNS-II	I.D. # 2299 (SILAS MASON HANGER PANTEX LOT 6348-074-001)	100.0	0.0	(c)	(c)
HNS-I	(BRITISH - PERME 343)	97.2	2.5	0.1	0.1

⁽a) I.D. # IS NSWC IDENTIFICATION NUMBER

⁽b) UNRESOLVED PEAK AREAS OF TNB AND PICOOH (NO PICOOH DETECTED BY TLC)

⁽c) TRACE = < 0.1 %

⁽d) NSWC LABORATORY SAMPLE

⁽e) J.C. DACONS, THIS LABORATORY, UNPUBLISHED RESULTS-FINE PARTICLE SIZE HNS MADE FROM HNS-II BY PRECIPITATION FROM HNO₃

CONDITIONS

COLUMN PARTISIL -10 ODS-2

(REVERSE PHASE)

SAMPLE 100µI DMSO

RANGE 04

RATE 2.0 ML/MINUTE

SOLVENT 40% METHANOL/60% H₂O




FIGURE 1 HPLC TRACE OF DMSO





FIGURE 2 HPLC TRACE OF A SYNTHETIC MIXTURE OF POTENTIAL HNS IMPURITIES






FIGURE 4 HPLC TRACE OF A SYNTHETIC MIXTURE OF POTENTIAL HNS IMPURITIES

CONDITIONS

COLUMN PARTISIL -10 ODS-2

(REVERSE PHASE)

RATE 5.0 ML/MINUTE

RANGE 08

PRESSURE 5000 PSI

SAMPLE SYNTHETIC MIXTURE

SAMPLE VOL. 50µl

SOLVENT 40% METHANOL/60% H₂O




FIGURE 5 HPLC TRACE OF A SYNTHETIC MIXTURE OF POTENTIAL HNS IMPURITIES

NSWC/WOL TR 77-154

DISTRIBUTION	Copies
Commander Naval Sea Systems Command Attn: SEA-0332 SEA-09G32 (Technical Library) Department of the Navy Washington, D. C. 20362	2
Office of Naval Research Attn: ONR-715 (Technical Library) 801 N. Quincy Street Arlington, VA 22217	2
Chief of Naval Operations Washington, D. C. 20360	
Commander Naval Weapons Center Attn: Technical Library China Lake, CA 93555	
Commanding Officer Naval Ordnance Station Attn: W. Carr Indian Head, MD 20640	
Commanding Officer Naval Academy Attn: Hd. Weps Dept Annapolis, MD 21402	
Superintendent Naval Postgraduate School Monterey, CA 93940	
Commanding Officer Naval Weapons Station Attn: Technical Library W. McBride	

Commanding Officer Naval Weapons Support Center Crane, IN 47522

DISTRIBUTION

Copies

Director Strategic Systems Projects Office Attn: SSPO-2731 (M. Baron) Department of the Navy Washington, D. C. 20376

Commander
Naval Air Systems Command
Attn: AIR-1116 (P. Facas)
Washington, D. C. 20361

Commanding Officer
Ballistics Research Laboratory
Attn: Technical Library
Aberdeen Proving Ground
Aberdeen, MD 21005

Commanding General Army Materiel Command Department of the Army Washington, D. C. 20316

Commander Army Rocket and Missile Agency Redstone Arsenal Huntsville, AL 35809

Director
Defense Documentation Center
Attn: TIPCR
Cameron Station
Alexandria, VA 22314

Commander
Systems Engineering Group
Attn: RTD
Wright-Patterson Air Force Base, OH 45433

Chief of Staff U. S. Air Force Attn: AFORD-AR Washington, D. C. 20350 12

DISTRIBUTION

Copies

Lyndon B. Johnson Space Center National Aeronautics & Space Administration Attn: Technical Library

T. Graves/EP4
J. Wheeler/AT3

R. Shirkey/JM6

C. S. Parks/BC73(40)

2101 Webster-Seabrook Road Houston, TX 77058

George C. Marshall Space Flight Center National Aeronautics & Space Administration Technical Library Attn: Robert White/EP-14

University of California Lawrence Radiation Laboratory Attn: Milton Finger

Walter Selig P.O. Box 808

Huntsville, AL 35812

Livermore, CA 94550

Chemtronics Attn: Technical Library Old Bee Tree Road Swannanoa, NC 28778

Ensign Bickford Company Attn: B. Boggs 660 Hopmeadow Street Simsbury, CT 06070

Explosive Technology Attn: F. Burkdoll P.O. Box KK Fairfield, CA 94533

General Dynamics Attn: W. Early (MZ2843) P. O. Box 748 Forth Worth, TX 76101

DISTRIBUTION

Copies

Grumman Aerospace Corporation Attn: J. Hopkins South Oyster Bay Road Bethpage, NY 11714

Lockheed Missiles & Space Corporation Attn: W. Gans P.O. Box 504 Sunnyvale, CA 94086

Los Alamos Scientific Laboratory Attn: Dr. L. Smith P.O. Box 1663 Los Alamos, NM 87544

McDonnell Douglas Corporation Attn: M. Schimmel P.O. Box 516 St. Louis, MO 63166

Ordnance Engineering Associates Attn: Ahmed Kafadar 1030 East North Avenue Des Plaines, IL 60016

Sandia Corporation Attn: Dr. N. Brown P.O. Box 5400 Albuquerque, NM 87115

Space Ordnance Systems, Inc. Attn: Dr. N. Zable 375 Santa Trinita Sunnyvale, CA 94006

Teledyne McCormick Selph Attn: R. Allen P.O. Box 6 Hollister, CA 95023 TO AID IN UPDATING THE DISTRIBUTION LIST FOR NAVAL SURFACE WEAPONS CENTER, WHITE OAK LABORATORY TECHNICAL REPORTS PLEASE COMPLETE THE FORM BELOW:

TO ALL HOLDERS OF NSWC/WOL TR 77-154
by Eleonore G. Kayset, Code CR-11
DO NOT RETURN THIS FORM IF ALL INFORMATION IS CURRENT

NEW ADDRESS (Show Zip Code)	
ATTENTION LINE ADDRESSES:	
_ REMOVE THIS FACILITY FROM THE	DISTRIBUTION LIST FOR TECHNICAL REPORTS ON THIS SUBJECT.

ED S